

Testing Laboratory

Accreditation Certificate

Accreditation No. RTL00430



JAB



Kobe Material Testing Laboratory Co., Ltd.

***47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155
Japan***

meets the following criteria. On the basis of this, Japan Accreditation Board (JAB) grants accreditation to the said testing laboratory.

Applicable accreditation criteria	: JIS Q 17025:2018 (ISO/IEC 17025:2017)
Scope of accreditation	: Mechanical testing, Chemical testing (As described in the appendix)
Premises covered by accreditation	: As described in the appendix.
Expiry date of accreditation	: June 30, 2022

Revised (28)	October 1, 2020
Renewed (6)	April 23, 2018
Initial accreditation	June 5, 1998

Y. Iizuka, President

Japan Accreditation Board

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 1/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

1) Premises on which testing activities are performed

Name of Premises	Harima Workshop	
Address of Premises	Postal code	675-0155
	Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, Japan
Testing service at permanent facilities or on site testing service	<input checked="" type="checkbox"/> Testing service at permanent facilities <input type="checkbox"/> On site testing service	

Scope of Accreditation

FIELD	M25 Mechanical Testing
CODE OF CIT*1	M25.A1.1
NAME OF CIT	Iron and Steel/Non-ferrous Metal

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	TEST METHOD STANDARD OR STANDARD OPERATING PROCEDURE (SECTION NO. LIMITED OR EXCLUDED)	TEST CONDITION etc.
B13.1 Tensile Testing	JIS Z 2241	Test force: Under 1000 kN
	ASTM E8/E8M	Test force: Under 100 kN
	ISO 6892-1	Test temperature: 23±5 °C Test force: Under 1000 kN
	JIS G 0567, ISO 6892-2	Test temperature: 35 °C to 1100 °C, excl Test force: Under 100 kN
	EN 10002-5, ASTM E21	Test temperature: 100 °C to 900 °C, excl Test force: Under 100 kN
	ISO 6892-3	Test temperature: -150 °C to 10 °C Test force: Under 300 kN
	ISO 5178	Test temperature: -196 °C (cooled in liquid nitrogen), -150 °C to 1100 °C Test force: Under 300 kN
	JIS Z 3121, ISO 4136, EN 895	Test category: Tensile test Test temperature: 23±5 °C Test force: Under 1000 kN

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 2/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Nuijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT ²	TEST METHOD STANDARD OR STANDARD OPERATING PROCEDURE (SECTION NO. LIMITED OR EXCLUDED)	TEST CONDITION etc.
	ASTM B557	Test force: Under 100 kN Test temperature: 23±5 °C
	ASTM B557M	Test force: Under 100 kN Test temperature: 23±5 °C
B13.3.1 Bend testing	JIS Z 2248 ISO 7438	Press bend method Test temperature: 23±5 °C Test force: Under 1000 kN Thickness: 3 mm to 30 mm
	JIS Z 3122 ISO 5173	Test specimen: Side bend. Face bend. Root bend Test force: 1000 kN Thickness: 3 mm to 30 mm
	EN 910	Roller bend method Test specimen: Side bend. Face bend. Root bend Test temperature: 23±5 °C Test force: 1000 kN Thickness: 10 mm to 30 mm
B13.4.1 Charpy impact test	JIS Z 2242, EN 10045-1, ISO 148-1	Test temperature: -196 °C (cooled in liquid nitrogen), -130 °C to 150 °C K2 up to 300 J
	ASTM E23	Capacity: Up to 500 J Test temperature: -196 °C (cooled in liquid nitrogen), -130 °C to 150 °C
B13.6.1 Brinell hardness test	JIS Z 2243-1, JIS Z 2243-2 ASTM E10	Brinell hardness: 20 HBW 10/500 to 650 HBW 10/3000
B13.6.2 Vickers hardness test	JIS Z 2244, ISO 6507-1, ISO 6507-4	Vickers hardness: 80 HV to 900 HV Test force: 0.9807 N to 9.807 N Test force: 49.03 N to 490.3 N
	ASTM E384 (except Knoop hardness)	Vickers hardness: 50 HV to 900 HV Test force: 0.9807 N to 9.807 N
	ASTM E92 (except Knoop hardness)	Vickers hardness: 80 HV to 900 HV Test force: 49.03 N to 490.3 N

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 3/11)

Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT*2	TEST METHOD STANDARD OR STANDARD OPERATING PROCEDURE (SECTION NO. LIMITED OR EXCLUDED)	TEST CONDITION etc.
B13.6.3 Rockwell hardness test	JIS Z 2245	Rockwell hardness: 10 HRC to 70 HRC Rockwell hardness: 20 HRBW to 100 HRBW
	ASTM E18	Rockwell hardness: 10 HRC to 70 HRC Rockwell hardness: 20 HRBW to 100 HRBW
B13.5.1 Fracture toughness testing	JIS G 0564, ASTM E399	Test specimen: CT specimen Test temperature: Normal temperature Test force: Up to 300 kN
	ASTM E1820, ASTM E1921	Test specimen: CT specimen Test temperature: -165 °C to 800 °C Test force: Up to 300 kN
B13.5.2 Drop-Weight test	ASTM E208	Capacity: Up to 550 J Test temperature: -80 °C to 0 °C
B13.16.1 Tensile creep testing	JIS Z 2271, ASTM E139, ASTM E292	Test temperature: 100 °C to 1100 °C Test force: 0.5 kN to 30.0 kN
B2.1 Metallographic test	ASTM E3	
B2.1.1 Macroscopic examination	JIS G 0553, ASTM E 340, EN 1321, ISO 17639	
B2.1.2 Microscopic examination	ASTM E407, EN 1321 ISO 17639	
B2.1.3 Grain size determination	JIS G 0551, NF EN ISO 643 (Specimen adjustment: except heat treatment method) (Evaluation method: except counting method)	
	ASTM E112 (Specimen adjustment: except heat treatment method) (Evaluation method: except planimetric procedure)	

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 4/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT ²	TEST METHOD STANDARD OR STANDARD OPERATING PROCEDURE (SECTION NO. LIMITED OR EXCLUDED)	TEST CONDITION, etc.
	ASTM E930	
B2.1.4 Microscopic test for the non-metallic inclusions	JIS G 0555	
	ASTM E45 method A, method D	
B13.15.1 High-cycle fatigue testing	ASTM E466	Control waveform: Triangular wave, sine wave, trapezoidal wave Test temperature: Room temperature to 1150 °C Test force: Up to 200 kN
B13.15.2 Low-cycle fatigue testing	JIS Z 2279	Control waveform: Triangular wave, sine wave Test temperature: Room temperature to 1150 °C Test force: Up to 200 kN
	ASTM E606/E606M	Control waveform: Triangular wave, sine wave, trapezoidal wave Test temperature: Room temperature to 1150 °C Test force: Up to 200 kN
B13.15.6 Crack growth test	ISO 12108	Test specimen: CT, CCT specimens Propagation rate: 10-5 mm/cycle and over Crack length measuring method: Compliance method and measurement with 20x magnifier Test temperature: Room temperature to 900 °C (induction heating) Test force: Up to 70 kN
	ASTM E647	Test specimen: CT, MT specimens Propagation rate: 10-5 mm/cycle and over Crack length measuring method: Compliance method and measurement with 20x magnifier Test temperature: Room temperature to 900 °C (induction heating) Test force: Up to 70 kN

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 5/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

Scope of Accreditation

FIELD	M25 Mechanical Testing
CODE OF CIT*1	M25.A1.2
NAME OF CIT	Fasteners

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B2.2.2 Determination of decarburized depth	JIS B 1051 (9.10.2) Microscopic Method	

Scope of Accreditation

FIELD	M25 Mechanical Testing
CODE OF CIT*1	M25.A2.1
NAME OF CIT	Plastics

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B13.1 Plastics Tensile Testing	JIS K 7161-1, JIS K 7161-2 (except Poisson's ratio)	Test specimen: Type 1A, Type 1B Test material: Applicable to JIS K 7162 Test temperature: 23±2 °C Test force: 4 N to 10 kN Strain rate: Under 400 %
B13.3.1 Plastics Bend testing	JIS K 7171	Test specimen: Test specimen recommended in 6.1.2 Test temperature: 23±2 °C Test force: 4 N to 10 kN
B13.4.1 Plastics Charpy impact test	JIS K 7111-1	Test specimen: Type 1 Hammer weight: 0.5, 1, 2, 4, 7.5, 15 (J) Test temperature: 23±2 °C Hammering direction: Edgewise
B13.4.2 Plastics Izod impact	JIS K 7110	Test specimen: Type 1 Hammer weight: 1, 2.75, 5.5, 11, 22 (J)

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 6/11)

Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Nijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
strength test		Test temperature: 23±2 °C
B13.6.3 Plastics Rockwell hardness test	JIS K 7202-2	Rockwell hardness: 50 HRR to 115 HRR Rockwell hardness: 50 HRM to 115 HRM Test temperature: 23±2 °C

Scope of Accreditation

FIELD	M25 Mechanical Testing
CODE OF CIT*1	M25.A13
NAME OF CIT	Composite Material

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B13.1 Tensile strength & elongation test	ASTM D3039/D3039M (except Poisson's Ratio , Transition Strain)	Test force: Under 100 kN Test temperature: -60 °C to 100 °C
B13.2.1 Uniaxial compression	SACMA SRM1R ASTM D6641/D6641M (except Poisson's Ratio)	Test force: Under 100 kN Test temperature: -60 °C to 100 °C
B13.8.2 Shear characteristic test	ASTM D2344/D2344M ASTM D3518/D3518M	Test force: Under 100 kN Test temperature: -60 °C to 100 °C

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 7/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

1) Premises on which testing activities are performed

Name of Premises	Harima Workshop		
Address of Premises	Postal code	675-0155	
	Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, Japan	
Testing service at permanent facilities or on site testing service	<input checked="" type="checkbox"/> Testing service at permanent facilities <input type="checkbox"/> On site testing service		

Scope of Accreditation

FIELD	M26 Chemical Testing
CODE OF CIT*1	M26.A1
NAME OF CIT	Metal, Material of metal, Metal Products

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B1.2 Volumetric analysis I (titration)	$8.05 \% \leq \text{Ni} \leq 14.26 \%$	JIS G 1216 4.(2)
B1.2 Volumetric analysis I(Redox titration)	$16.11 \% \leq \text{Cr} \leq 30.00 \%$	JIS G 1217 4. a)
B2.1 Absorptiometric analysis: Infrared spectrophotometric analysis	$0.01 \% \leq \text{C} \leq 0.50 \%$	JIS G 1211-3 [except 8.4 a), b)]
	$0.001 \% \leq \text{S} \leq 0.30 \%$	JIS G 1215-4 (except 7.6.1, 7.6.2)
B2.1 Absorptiometric analysis: UV-visible spectroscopy	$0.05 \% \leq \text{Si} \leq 1.00 \%$	JIS G 1212 4. (3)
	$0.005 \% \leq \text{P} \leq 0.040 \%$	JIS G 1214 4. a)
	$0.14 \% \leq \text{Mn} \leq 1.5 \%$	JIS G 1213 4. b)

Accreditation Certificate

Appendix

(Page 8/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Nuijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B2.4 Emission Spectrochemical analysis: ICP-AES	$0.01 \% \leq \text{Mo} \leq 0.48 \%$	JIS G 1258-1
	$0.01 \% \leq \text{Mn} \leq 10.0 \%$	JIS G 1258-2
	$0.01 \% \leq \text{Mo} \leq 10.0 \%$	
	$0.01 \% \leq \text{Cu} \leq 10.0 \%$	
	$0.01 \% \leq \text{Co} \leq 10.0 \%$	
	$0.01 \% \leq \text{Nb} \leq 10.0 \%$	
	$0.01 \% \leq \text{Ni} \leq 10.0 \%$	
	$0.01 \% \leq \text{Cr} \leq 10.0 \%$	
	$0.001 \% \leq \text{B} \leq 0.010 \%$	JIS G 1258-5
	$0.01 \% \leq \text{Al} \leq 2.00 \%$	JIS G 1258-3* : Partially modified (Upper limit of quantitation range extended)
B4.3 Thermal conductivity measurement : Thermal conductivity method	$0.010 \% \leq \text{N} \leq 0.045 \%$	JIS G 1228 4. d)

Scope of Accreditation

FIELD	M26 Chemical Testing
CODE OF CIT*1	M26.A1
NAME OF CIT	Metal (Nickel alloy)

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B1.2 Volumetric analysis I (titration)	$32.80 \% \leq \text{Ni} \leq 73.43 \%$	JIS G 1216 4.(2) * : Partially modified (Upper limit of quantitation range extended)
B1.2 Volumetric analysis I (Redox titration)	$11.35 \% \leq \text{Cr} \leq 35.00 \%$	JIS H 1279 4. b) * : Partially modified (Upper limit of quantitation range extended)

Accreditation Certificate

Appendix

(Page 9/11)

Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT ²	PROPERTIES MEASURED	TEST METHOD STANDARD / STANDARD OPERATING PROCEDURE
B2.1 Absorptiometric analysis: Infrared spectrophotometric analysis	$0.004\% \leq C \leq 0.082\%$	JIS H 1275 4. e)
	$0.001\% \leq S \leq 0.012\%$	JIS H 1277 4. d)
B2.1 Absorptiometric analysis: UV-visible spectroscopy	$0.05\% \leq Si \leq 1.00\%$	JIS H 1276 4. b)
	$0.005\% \leq P \leq 0.030\%$	JIS H 1278 4. a)
B2.4 Emission Spectrochemical analysis: ICP-AES	$0.01\% \leq Nb \leq 5.00\%$ $0.01\% \leq Ta \leq 1.00\%$	JIS H 1289
	$0.01\% \leq Mn \leq 5.00\%$ $0.01\% \leq Mo \leq 1.00\%$ $0.01\% \leq Cu \leq 1.00\%$ $0.01\% \leq Co \leq 1.00\%$ $0.01\% \leq Ti \leq 5.00\%$ $0.01\% \leq Al \leq 5.00\%$ $1.00\% \leq Fe \leq 20.0\%$ $0.001\% \leq B \leq 0.020\%$	JIS H 1289* : Partially modified (Measurement components added)
B4.3 Thermal conductivity measurement : Thermal conductivity method	$0.006\% \leq N \leq 0.073\%$	JIS G 1228 4. d)

Accreditation Certificate

Appendix

(Page 10/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

1) Premises on which testing activities are performed

Name of Premises	Hitachi Minami Laboratory, Ibaraki Workshop	
Address of Premises	Postal code	319-1231
	Address	1270-60, Tome-cho, Hitachi-shi, Ibaraki, Japan
Testing service at permanent facilities or on site testing service	<input checked="" type="checkbox"/> Testing service at permanent facilities <input type="checkbox"/> On site testing service	

Scope of Accreditation

FIELD	M25 Mechanical Testing
CODE OF CIT*1	M25.A1.1
NAME OF CIT	Iron and Steel/Non-ferrous Metal

*1 CIT: Classification of Item to be Tested

*2 TCT: Technical Classification of Test

CODE & NAME OF TCT*2	TEST METHOD STANDARD OR STANDARD OPERATING PROCEDURE (SECTION NO. LIMITED OR EXCLUDED)	TEST CONDITION etc.
B13.1 Tensile Testing	JIS Z 2241, ASTM E8/E8M	Test force: Under 100 kN
	JIS G 0567, ASTM E21	Test temperature: 100 °C to 900 °C, excl Test force: Under 100 kN
	JIS Z 3121	Test category: Tensile test Test temperature: 23±5 °C Test force: Under 1000 kN
B13.3.1 Bend testing	JIS Z 3122	Test specimen: Side bend. Face bend. Root bend Test force: 1000 kN Thickness: 3 mm to 30 mm
B13.4.1 Charpy impact test	JIS Z 2242	Test temperature: -196 °C (cooled in liquid nitrogen), -130 °C to 150 °C K2 up to 300 J
B13.6.1 Brinell hardness test	JIS Z 2243-1, JIS Z 2243-2 ASTM E10	Brinell hardness: 20 HBW 10/500 to 650 HBW 10/3000
B13.6.2 Vickers hardness test	JIS Z 2244, ASTM E92 (except Knoop hardness)	Vickers hardness: 80 HV to 900 HV Test force: 49.03 N to 490.3 N

Accreditation No.

RTL00430

Accreditation Certificate

Appendix

(Page 11/11)



JAB



Type of Laboratory	Testing Laboratory
Name of Laboratory	Kobe Material Testing Laboratory Co., Ltd.
Address	47-13, Niijima, Harima-cho, Kako-gun, Hyogo, 675-0155 Japan

CODE & NAME OF TCT ²	TEST METHOD STANDARD OR STANDARD OPERATING PROCEDURE (SECTION NO. LIMITED OR EXCLUDED)	TEST CONDITION etc.
B13.6.3 Rockwell hardness test	JIS Z 2245	Rockwell hardness: 10 HRC to 70 HRC Rockwell hardness: 20 HRBW to 100 HRBW
	ASTM E18	Rockwell hardness: 10 HRC to 70 HRC
B13.5.1 Fracture toughness testing	ASTM E399	Test specimen: CT specimen Test temperature: Normal temperature Test force: Up to 300 kN
B13.15.1 High-cycle fatigue testing	ASTM E466	Control waveform: Triangular wave, sine wave, trapezoidal wave Test temperature: Room temperature to 1150 °C Test force: Up to 80 kN
B13.15.2 Low-cycle fatigue testing	JIS Z 2279	Control waveform: Triangular wave, sine wave Test temperature: Room temperature to 1150 °C Test force: Up to 80 kN
	ASTM E606/E606M	Control waveform: Triangular wave, sine wave, trapezoidal wave Test temperature: Room temperature to 1150 °C Test force: Up to 80 kN

Japan Accreditation Board